


LOD 123: Making the semantic web easier to use

Tim Finin

University of Maryland, Baltimore County

Joint work with Lushan Han, Varish Mulwad, Anupam Joshi

Overview



- Linked Open Data 101
- Two ongoing UMBC dissertations
 - Varish Mulwad, Generating linked data from tables
 - Lushan Han, Querying linked data with a quasi-NL interface

Linked Open Data (LOD)



- Linked **data** is just RDF data, typically just the instances (ABOX), not schema (TBOX)
- RDF data is a graph of triples
 - URI URI string
dbr:Barack_Obama dbo:spouse “Michelle Obama”
 - URI URI URI
dbr:Barack_Obama dbo:spouse dbpedia:Michelle_Obama
- Best **linked** data practice prefers the 2nd pattern, using nodes rather than strings for “entities”
- Liked **open** data is just linked data freely accessible on the Web along with any required ontologies

Semantic Web

Use Semantic Web Technology
to publish shared data &
knowledge


Semantic web technologies
allow machines to share data
and knowledge using common
web language and protocols.

~ 1997

Semantic Web beginning

Semantic Web => Linked Open Data

Use Semantic Web Technology
to publish shared data &
knowledge




2007

Data is inter-
linked to support inte-
gration and fusion of knowledge

LOD beginning

Semantic Web => Linked Open Data

Use Semantic Web Technology
to publish shared data &
knowledge




2008

Data is inter-
linked to support inte-
gration and fusion of knowledge

LOD growing

Semantic Web => Linked Open Data

Use Semantic Web Technology to publish shared data & knowledge



2009


Data is inter-linked to support integration and fusion of knowledge

... and growing

Linked Open Data

Use Semantic Web Technology to publish shared data & knowledge

LOD is the new Cyc: a common source of background knowledge



Data is inter-linked to support integration and fusion of knowledge


2010

...growing faster

Linked Open Data

Use Semantic Web Technology
to publish shared data &
knowledge

LOD is the new Cyc: a common
source of background
knowledge



Data is inter-
linked to support inte-
gration and fusion of knowledge

2011: 31B facts in 295 datasets interlinked by 504M assertions on ckan.net

Exploiting LOD not (yet) Easy



- Publishing or using LOD data has inherent difficulties for the potential user
 - It's difficult to explore LOD data and to **query** it for answers
 - It's challenging to **publish** data using appropriate LOD vocabularies & link it to existing data
- Problem: $O(10^4)$ schema terms, $O(10^{11})$ instances
- I'll describe two ongoing research projects that are addressing these problems

Generating Linked Data by Inferring the Semantics of Tables

Research with Varish Mulwad


<http://ebiq.org/j/96>

Early work



- Mapping tables to RDF led to early tools
 - D2RQ (2006) relational tables to RDF
 - RDF 123 (2007) spreadsheet to RDF
- And a recent W3C standard
 - R2RML (2012) a W3C recommendation
- But none of these can automatically generate high-quality linked data
 - They don't link to LOD classes and properties nor recognize entity mentions

Goal: Table => LOD*



* DBpedia

Goal: Table => LOD*

Name	Team	Position	Height
Michael Jordan	Chicago	Shooting guard	1.98
Allen Iverson	Philadelphia	Point guard	1.83
Yao Ming	Houston		
Tim Duncan	San Antonio		

@prefix dbpedia: <http://dbpedia.org/resource/> .
@prefix dbo: <http://dbpedia.org/ontology/> .
@prefix yago: <http://dbpedia.org/class/yago/> .

**RDF
Linked
Data**

"Name"@en is rdfs:label of dbo:BasketballPlayer .

"Team"@en is rdfs:label of yago:NationalBasketballAssociationTeams .

"Michael Jordan"@en is rdfs:label of dbpedia:Michael Jordan .

dbpedia:Michael Jordan a dbo:BasketballPlayer .

"Chicago Bulls"@en is rdfs:label of dbpedia:Chicago Bulls .

dbpedia:Chicago Bulls a yago:NationalBasketballAssociationTeams .



All this in a completely automated way

Tables are everywhere !! ... yet ...



The web – **154 million**
high quality relational
tables



Table 1—Characteristics and fasting lipid profiles of African-American and Caucasian patients with type 2 diabetes

	African-Americans			Caucasians		
	Both	Men	Women	Both	Men	Women
n	4,014	1,427	2,572	328	141	187
Age (years)	53 ± 0.2	52 ± 0.3	54 ± 0.3*	54 ± 0.6	54 ± 0.9	54 ± 0.9
Diabetes duration (years)	5.2 ± 0.1	4.9 ± 0.2	5.3 ± 0.2*	5.9 ± 0.4	5.6 ± 0.6	6.1 ± 0.6
BMI (kg/m ²)	33 ± 0.1	31 ± 0.2	34 ± 0.2*	33 ± 0.4	32 ± 0.6	34 ± 0.6*
HbA _{1c} (%)	9.3 ± 0.04†	9.4 ± 0.1	9.2 ± 0.1	8.6 ± 0.1	8.5 ± 0.2	8.7 ± 0.2
Fasting plasma glucose (mg/dl)	191 ± 1.3†	187 ± 2.3	193 ± 1.6*	204 ± 4.3	191 ± 6.3	213 ± 5.8*
Percentage on each therapy						
Diet	24.2	20.1				
Sulfonylurea						



Table 2. Results in the intent-to-treat population

	Omeprazole Oral Suspension (n = 178)	Intravenous Cimetidine (n = 181)	Confidence Interval for the Difference in Rates, %
Clinically significant bleeding, n (%)	7 (3.9)	10 (5.5)	-100.0, 2.8 ^a
Any overt bleeding, n (%)	34 (19.1)	58 (32.0)	-21.9, -4.0 ^b
Inadequate pH control, n (%)	32 (18.0)	105 (58.0)	-49.2, -30.9 ^c

Evidence-based medicine

Evidence-based medicine judges the efficacy of treatments or tests by meta-analyses of clinical trials. Key information is often found in **tables in articles**

Table 2. Results in the intent-to-treat population

	Omeprazole Oral Suspension (n = 178)	Intravenous Cimetidine (n = 181)	Confidence Interval for the Difference in Rates, %
Clinically significant bleeding, n (%)	7 (3.9)	10 (5.5)	-100.0, 2.8 ^a
Any overt bleeding, n (%)	34 (19.1)	58 (32.0)	-21.9, -4.0 ^b
Inadequate pH control, n (%)	32 (18.0)	105 (58.0)	

of Clinical trials published in 2008

TABLE 1. Characteristics of Postmenopausal Women with a First Venous Thrombosis and Control Subjects

Characteristic	477 Cases	1986 Control Subjects	P
Age, mean (SD)* years	70.9 (11.2)	69.0 (9.6)	<0.001
Non-white, %	6.1	12.5	0.3
Time enrolled in GHC,† mean (SD) years	22.4 (12.7)	23.4 (11.6)	0.8
Postmenopausal hormone therapy, %	37.1	36.5	0.01
Body mass index, mean (SD) kg/m ²	28.7 (7.9)	27.8 (6.3)	<0.001
Hospitalization in prior 3 months, %	31.2	2.2	<0.001
Major fracture in prior 3 months, %	5.2	0.9	<0.001
Malignancy, %	35.6	12.2	<0.001
Vascular disease,‡ %	31.5	19.8	<0.001
Vascular procedures,§ %	1.0	0.1	<0.001

of meta analysis published in 2008

Table 3. Percentage and number of patients with median gastric pH ≤ 4 by trial day

Trial Day	Omeprazole Oral Suspension, %	Intravenous Cimetidine, %	p Value
1	2.4 (4/166)	11.5 (20/174)	<.01
2	0.6 (1/170)	10.3 (18/175)	<.01
3	2.8 (4/143)	17.8 (28/157)	<.01
4	4.0 (5/124)	13.1 (16/122)	.01
5	2.8 (3/109)	15.5 (16/103)	<.01
6	2.2 (2/89)	20.5 (18/88)	<.01
7	1.4 (1/73)	17.9 (14/78)	<.01
8	5.0 (3/60)	24.3 (17/70)	<.01
9	3.8 (2/53)	32.2 (19/59)	<.01
10	4.7 (2/43)	33.3 (17/51)	<.01
11	5.0 (2/40)	30.4 (14/46)	<.01
12	0.0 (0/35)	25.6 (10/39)	<.01
13	0.0 (0/31)	27.3 (9/33)	<.01
14	3.7 (1/27)	28.6 (8/28)	.02

Pre-dose pH measurements on day 1 were excluded from the median calculation.




~ 400,000 datasets 👍😊

~ **< 1** % in RDF


2010 Preliminary System

T2LD Framework

Predict Class for
Columns



Linking the table
cells




Identify and
Discover relations

Class predict
Entity Linking

Examples of class labels

Column – Nationality
Prediction – MilitaryCo

Column – Birth Place
Prediction – Populated




Sources of Errors




- The *sequential* approach let errors percolate from one phase to the next
- The system was biased toward predicting overly general classes over more appropriate specific ones
- **Heuristics** largely drive the system
- Although we consider multiple sources of evidence, we did not **joint assignment**

A Domain Independent Framework



Query Mechanism



Ranking the candidates

- $C_i = \text{"State"} ; L_{Ci} = \text{AdministrativeRegion}$



String in column header



Class from an ontology

- $f_1 = [\text{Levenshtein distance}(C_i, L_{Ci}),$
Dice Score $(C_i, L_{Ci}),$
Semantic Similarity $(C_i, L_{Ci}),$
InformationGain(L_{Ci})]



String similarity metrics

- $\psi_1 = \exp(w_1^T f_1(C_i, L_{Ci}))$

Ranking the candidates

- $R_{ij} = \text{"Baltimore"} ; E_{ij} = \text{Baltimore_Maryland}$

String in table cell

Entity from the
knowledge base (KB)


- $f_2 = [\text{Levenshtein distance}(R_{ij}, E_{ij}),$
Dice Score (R_{ij}, E_{ij}),
PageRank (E_{ij}),
KBScore (E_{ij})
PageLength (E_{ij})]

String similarity
metrics

Popularity
metrics

$$\psi_2 = \exp(w_2^T f_2(R_{ij}, E_{ij}))$$


Joint Inference over evidence in a table




✓ Probabilistic Graphical Models

A graphical model for tables

Joint inference over evidence in a table




Parameterized graphical model



Challenge: Interpreting Literals

Many columns have literals, e.g., numbers



- Predict properties based on cell values
- Cyc had hand coded rules: *humans don't live past 120*
- We extract *value distributions* from LOD resources
 - Differ for subclasses: age of *people* vs. *political leaders* vs. *athletes*
 - Represent as *measurements*: value + units
- Metric: possibility/probability of values given distribution

Other Challenges



- Using table *captions* and other text is associated documents to provide context
- *Size* of some data.gov tables (> 400K rows!) makes using full graphical model impractical
 - *Sample* table and run model on the subset
- Achieving acceptable accuracy may require *human input*
 - 100% accuracy unattainable automatically
 - How best to let humans offer advice and/or correct interpretations?

PMI as an association measure


We use [pointwise mutual information](#) (pmi) to measure the association between two RDF resources (nodes)

$$\text{pmi}(x; y) \equiv \log \frac{p(x, y)}{p(x)p(y)} = \log \frac{p(x|y)}{p(x)} = \log \frac{p(y|x)}{p(y)}.$$

pmi is used for word association by comparing how often two words occur together in text to their expected co-occurrence if independent

PMI for RDF instances

- For text, the co-occurrence context is usually a window of some number of words (e.g, 50)
- For RDF instances, we count three graph patterns as instances of the co-occurrence of N1 and N2



- Other graph patterns can be added, but we've not evaluated their utility or cost to compute.

PMI for RDF types

- We also want to measure the association strength between *RDF types*, e.g., a `dbo:Actor` associated with a `dbo:Film` vs. a `dbo:Place`
- We can also measure the association of an RDF property and types, e.g. `dbo:author` used with a `dbo:Film` vs. a `dbo:Book`
- Such simple statistics can be efficiently computed for large RDF collections in parallel

PREFIX `dbo: <http://dbpedia.org/ontology/>`


GoRelations: Intuitive Query System for Linked Data

Research with Lushan Han

<http://ebiq.org/j/93>

Dbpedia is the Stereotypical LOD

- DBpedia is an important example of Linked Open Data
 - Extracts structured data from Infoboxes in Wikipedia
 - Stores in RDF using custom ontologies Yago terms
- The major integration point for the entire LOD cloud
- Explorable as HTML, but harder to query in SPARQL



DBpedia.org/page/Mark_Twain

dbpedia-owl:birthDate

1835-11-30 (xsd:date)

dbpedia-owl:birthName

Samuel Langhorne Clemens

dbpedia-owl:birthPlace

dbpedia:Florida,_Missouri

dbpedia:Missouri

dbpedia-owl:child

dbpedia:Jean_Clemens

dbpedia:Susy_Clemens

dbpedia:Clara_Clemens

dbpedia-owl:deathDate

1910-04-21 (xsd:date)

dbpedia-owl:deathPlace

dbpedia:Redding,_Connecticut

dbpedia:Connecticut

dbpedia-owl:genre

dbpedia:Essay

dbpedia:Historical_fiction

dbpedia:Social_commentary

dbpedia:Satire

dbpedia:Non-fiction

dbpedia:Philosophy_and_literature

dbpedia:Literary_criticism

dbpedia:Travel_literature

dbpedia:Fiction

dbpedia:Children's_literature

dbpedia-owl:notableWork

dbpedia:Adventures_of_Huckleberry_Finn

dbpedia:The_Adventures_of_Tom_Sawyer

dbpedia-owl:occupation

dbpedia:Writer

dbpedia:Lecture

dbpedia-owl:pseudonym

Mark Twain

dbpedia-owl:thumbnail

http://upload.wikimedia.org/wikipedia/commons/thumb/c/c5/Mark_Twain_by_AF_Bra

dbpedia-owl:wikiPageExternalLink

http://www.sfgate.com/cgi-bin/article.cgi?file=/c/a/2005/08/19/MNGOBEA9JI1.DTL

http://www.pbs.org/marktwain/scrapbook/index.html

http://www.kamakurapens.com/TwainsConklin.html

http://www.ucmerced.edu/faculty/facultybio.asp?facultyid=95

Browsing
DBpedia's
Mark Twain


34/49

Querying LOD is Much Harder

- Querying DBpedia requires a lot of a user
 - Understand the **RDF model**
 - Master **SPARQL**, a formal query language
 - Understand **ontology terms**: 320 classes & 1600 properties !
 - Know instance **URIs** (>1M entities !)
 - Term heterogeneity (Place vs. PopulatedPlace)

- Querying large LOD sets overwhelming

- Natural language query systems still a research goal



Goal



- Allow a user with a basic understanding of RDF to query DBpedia and ultimately distributed LOD collections
 - To explore what data is in the system
 - To get answers to question
 - To create SPARQL queries for reuse or adaptation
- Desiderata
 - Easy to learn and to use
 - Good accuracy (e.g., precision and recall)
 - Fast

Key Idea




Structured keyword queries

Reduce problem complexity by:

- User enters a *simple graph*, and
- Annotates the nodes and arcs with *words and phrases*

Structured Keyword Queries




- Nodes denote entities and links binary relations
- Entities described by two unrestricted terms:
name or value and *type* or concept
- Result entities marked with ? and those not with *
- A compromise between a natural language Q&A system and SPARQL
 - Users provide compositional structure of the question
 - Free to use their own terms in annotating the structure

Translation – Step One

finding semantically similar ontology terms


For each concept or relation in the graph, generate the k most semantically similar candidate ontology classes or properties



Similarity metric is **distributional similarity, LSA, and WordNet.**

Another Example

Football players who were born in the same place as their team's president



Translation – Step Two

disambiguation algorithm

- To assemble the best interpretation we rely on *statistics of the data*
- Primary measure is *pointwise mutual information* (PMI) between RDF terms in the LOD collection

This measures the degree to which two RDF terms occur together in the knowledge base

- In a reasonable interpretation, *ontology terms associate* in the way that their corresponding *user terms* connect in the structured keyword query

Translation – Step Two

disambiguation algorithm

Three aspects are combined to derive an *overall goodness measure* for each candidate interpretation

Joint disambiguation

$$\operatorname{argmax}_{p_1 \dots p_m \ c_1 \dots c_n \in H} \text{goodness}(G) = \operatorname{argmax}_{p_1 \dots p_m \ c_1 \dots c_n \in H} \sum_{i=1}^m \text{goodness}(L_i) \quad (1)$$

Resolving direction

$$\begin{aligned} &\text{If } [\overrightarrow{\text{PMI}}(c(O_i), p(R_i)) + \overrightarrow{\text{PMI}}(p(R_i), c(S_i))] \\ &\quad - [\overrightarrow{\text{PMI}}(c(S_i), p(R_i)) + \overrightarrow{\text{PMI}}(p(R_i), c(O_i))] > \alpha \\ &\quad \text{Then } S_i' = O_i, O_i' = S_i \\ &\quad \text{Else } S_i' = S_i, O_i' = O_i \end{aligned} \quad (2)$$


Link reasonableness

$$\begin{aligned} \text{goodness}(L_i) = & \max(\overrightarrow{\text{PMI}}(c(S_i'), p(R_i)) \cdot \text{sim}(S_i', c(S_i')) \cdot \text{sim}(R_i, p(R_i)) \\ & + \overrightarrow{\text{PMI}}(p(R_i), c(O_i')) \cdot \text{sim}(O_i', c(O_i')) \cdot \text{sim}(R_i, p(R_i)), \beta) \\ & + \text{PMI}(c(S_i'), c(O_i')) \cdot \text{sim}(S_i', c(S_i')) \cdot \text{sim}(O_i', c(O_i')) \end{aligned} \quad (3)$$

Example of Translation result

Concepts: Place => Place, Author => Writer, Book => Book

Properties: born in => birthPlace, wrote => author (inverse direction)




SPARQL Generation



The translation of a semantic graph query to SPARQL is straightforward given the mappings

Concepts

- Place => Place
- Author => Writer
- Book => Book



Relations

- born in => birthPlace
- wrote => author

```
PREFIX dbo: <http://dbpedia.org/ontology/>

SELECT DISTINCT ?x, ?y WHERE {
  ?0 a dbo:Book .
  ?0 rdfs:label ?label0 .
  ?label0 bif:contains "The adventures of Tom Sawyer" .
  ?x a dbo:Writer .
  ?y a dbo:Place .
  {?0 dbo:author ?x} .
  {?x dbo:birthPlace ?y} .
}
```

Evaluation



- 33 test questions from 2011 *Workshop on Question Answering over Linked Data* answerable using DBpedia
- Three human subjects unfamiliar with DBpedia translated the test questions into semantic graph queries
- Compared with two top natural language QA systems: [PowerAqua](#) and [True Knowledge](#)

		<i>Prec.</i>	<i>Recall</i>	<i>F</i>
GoRelations	regular	0.687	0.722	0.704
	concise	0.736	0.803	0.768
PowerAqua	1st triple	0.372	0.483	0.420
	all triples	0.334	0.483	0.395
	merged	0.255	0.291	0.272
True Knowledge		0.469	0.535	0.500

[Manual](#) [Experiments](#) [Q&A](#) [About](#)



Please input relations in your query. One per line.

?x/American Football Player, date of birth, ?y/Date
?x, height, ?z/Number

Examples: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [11](#) [12](#) [13](#) [14](#) [15](#) [16](#) [17](#) [18](#)

Query

Relaxed Query

See Translations

Message: This query gives data about the height of American football players and their date of birth. Football fans may feel it interesting to know how the height of football players changes over time.

<http://ebiq.org/GOR>

x	z	y
http://dbpedia.org/resource/Jack_Shapiro	1.5494	1907-03-22
http://dbpedia.org/resource/Josh_Betts	1.5748	1982-08-25
http://dbpedia.org/resource/Nate_Abrams	1.6256	1897-12-25
http://dbpedia.org/resource/Herbert_Clow	1.6256	1899-05-07
http://dbpedia.org/resource/Trindon_Holliday	1.651	1986-04-27
http://dbpedia.org/resource/Earl_Warweg	1.6764	1892-01-11
http://dbpedia.org/resource/Jacquizz_Rodgers	1.6764	1990-02-06
http://dbpedia.org/resource/John_Brallier	1.6764	1876-12-27
http://dbpedia.org/resource/Menz_Lindsey	1.6764	1897-07-25
http://dbpedia.org/resource/Stefan_Logan	1.6764	1981-06-02
http://dbpedia.org/resource/Cory_Ross	1.6764	1982-09-22
http://dbpedia.org/resource/Darren_Sproles	1.6764	1983-06-20
http://dbpedia.org/resource/Jack_Fleischman	1.6764	1901-08-15
http://dbpedia.org/resource/Eddie_Scharer	1.6764	1902-01-26
http://dbpedia.org/resource/John_Barrett_%28American_football%29	1.6764	1899-02-25
http://dbpedia.org/resource/Dick_Thornton_%28American_football%29	1.6764	1908-02-04
http://dbpedia.org/resource/Walter_French_%28baseball%29	1.7018	1899-07-12
http://dbpedia.org/resource/Al_Loeb	1.7018	1890-03-11
http://dbpedia.org/resource/Antwaun_Carter	1.7018	1981-09-09
http://dbpedia.org/resource/Terry_Caulley	1.7018	1984-06-22
http://dbpedia.org/resource/Kendall_Hunter	1.7018	1988-09-16
http://dbpedia.org/resource/LaRod_Stephens-Howling	1.7018	1987-04-26
http://dbpedia.org/resource/Jayson_Foster	1.7018	1985-07-22
http://dbpedia.org/resource/Mark_McMillian	1.7018	1970-04-29
http://dbpedia.org/resource/Al_Cornsweet	1.7018	1906-07-16
http://dbpedia.org/resource/Bodie_Weldon	1.7018	1895-11-07
http://dbpedia.org/resource/Bill_Stobbs	1.7018	1896-05-28
http://dbpedia.org/resource/Johnny_Bryan	1.7018	1897-02-28
http://dbpedia.org/resource/Andrew_Hawkins	1.7018	1986-03-10
http://dbpedia.org/resource/Chad_Owens	1.7018	1982-04-03
http://dbpedia.org/resource/Mark_Higgs	1.7018	1966-04-11
http://dbpedia.org/resource/Emmett_McLemore	1.7018	1899-02-25
http://dbpedia.org/resource/Danny_Woodhead	1.7018	1955-01-25
http://dbpedia.org/resource/Garrett_Wolfe	1.7018	1984-08-17
http://dbpedia.org/resource/Shaud_Williams	1.7018	1980-02-10

<http://ebiq.org/GOR>

Three Top Interpretations of the User Query

Top One Interpretation

Before Step Three

```
* ?x/American Football Player has a candidate list including 0:AmericanFootballPlayer 1.00 1:Person 0.25 (the selected choice is AmericanFootballPlayer 1.00)
* ?z/Number has a candidate list including 0:Number 1.00 1:#Group 0.31 2:#Code 0.31 3:EthnicGroup 0.25 4:#Size 0.23 5:#Series 0.23 6:Single 0.21 7:OlympicResult 0.15 8:MountainRange 0.14 (the selected choice is Number 1.00)
* ?y/Date has a candidate list including 0:Date 1.00 1:Grape 0.19 2:Holiday 0.18 3:Name 0.18 4:Place 0.15 5:Event 0.15 6:#Era 0.15 7:GivenName 0.15 8:HistoricPlace 0.14 9:WrestlingEvent 0.14 10:PopulatedPlace 0.12 11:SportsEvent 0.12 12:WorldHeritageSite 0.12 13:NaturalPlace 0.12 14:MixedMartialArtsEvent 0.11 (the selected choice is Date 1.00)
```

After Step Three

```
* ?x/American Football Player => AmericanFootballPlayer
* ?z/Number => Number
* ?y/Date => Date
& ?x/American Football Player:date of birth: ?y/Date => 0:@birthDate 1.00
& ?x/American Football Player:height: ?z/Number => 0:@height 1.00
```

The Regular SPARQL Query

```
PREFIX dbo: <http://dbpedia.org/ontology/>

SELECT DISTINCT ?x, ?z, ?y WHERE {
  ?x a dbo:AmericanFootballPlayer .
  ?x dbo:birthDate ?y .
  ?x dbo:height ?z .
}
```

Query

The Concise SPARQL Query

```
PREFIX dbo: <http://dbpedia.org/ontology/>

SELECT DISTINCT ?x, ?z, ?y WHERE {
  ?x a dbo:AmericanFootballPlayer .
  ?x dbo:birthDate ?y .
  ?x dbo:height ?z .
}
```

Query

The Regular SPARQL Query

```
PREFIX dbo: <http://dbpedia.org/ontology/>

SELECT DISTINCT ?x, ?z, ?y WHERE {
  ?x a dbo:AmericanFootballPlayer .
  {{?x dbo:birthDate ?y}} .
  {{?x dbo:height ?z}} .
}
```

Query

The Concise SPARQL Query

```
PREFIX dbo: <http://dbpedia.org/ontology/>

SELECT DISTINCT ?x, ?z, ?y WHERE {
  ?x a dbo:AmericanFootballPlayer .
  {{?x dbo:birthDate ?y}} .
  {{?x dbo:height ?z}} .
}
```

Top Two Interpretation

Before Step Three

```
* ?x/American Football Player has a candidate list including 0:AmericanFootballPlayer 1.00 1:Person 0.25 (the selected choice is AmericanFootballPlayer 1.00)
* ?z/Number has a candidate list including 0:Number 1.00 1:#Group 0.31 2:#Code 0.31 3:EthnicGroup 0.25 4:#Size 0.23 5:#Series 0.23 6:Single 0.21 7:OlympicResult 0.15 8:MountainRange 0.14 (the selected choice is Number 1.00)
```

<http://ebiq.org/GOR>

```
* ?z/Number => #Series
* ?y/Date => Date
& ?x/American Football Player:date of birth: ?y/Date => 0:@birthDate 1.00
```

Current challenges



- Baseline system works well for DBpedia
- Current challenges we are addressing are
 - Adding direct entity matching
 - Relaxing the need for type information
 - Testing on other LOD collections and extending to a set of distributed LOD collections
 - Developing a better Web interface
 - Allowing user feedback and advice
- See <http://ebiq.org/93> for more information & try our alpha version at <http://ebiq.org/GOR>

Final Conclusions

- Linked Data is an emerging paradigm for sharing structured and semi-structured data
 - Backed by machine-understandable semantics
 - Based on successful Web languages and protocols
- Generating and exploring Linked Data resources can be challenging
 - Schemas are large, too many URIs
- New tools for mapping tables to Linked Data and translating structured natural language queries help reduce the barriers

<http://ebiq.org/>