



General ordering data

Order No.	1760510000
Article designation	PM 5.08/2/90 3.5 SW
Version	PCB terminal, Leaf spring connection, Soldered connection, Clamping range, max.: 2.5 mm ² , Pitch: 5.08 mm, Number of poles: 2, 90°, Box
EAN	4032248032488
Qty	500

System parameters

Series	PM series
Conductor connection system	Leaf spring connection
Fitted to PCB	Soldered connection
Outgoing direction of conductor	90°
Pitch	5,08 mm
Pitch in inch	0,200 inch
Number of poles	2
Fitted by customer	yes
Max. adjacent poles per row	24
No. of rows	1
Length of soldering post	3,5 mm
Dia. of fitting hole	1,3 mm
Fitting hole tolerance	+ 0.1 mm
No. of solder pins per pole	1
Screwdriver blade	0.6 x 3.5
Screwdriver blade standard	DIN 5264
Tightening torque, min.	0,4 Nm
Tightening torque, max.	0,5 Nm
Clamping screw	M 2.5
Stripping length	6 mm
L1 in mm	5,08 mm
L1 in inch	0,200 inch
Electric shock protection to DIN VDE 0470	IP 20
Electric shock protection to DIN VDE 0470	Safe from finger touch

Material data

Insulation material	Wemid (PA)
Colour	black
Description of plastic colour	ähnlich RAL 9011
Insulating material group	I
UL 94 combustibility class	V-0
CTI	>= 600
Contact base material	Cu alloy
Contact surface	tinned
Storage temperature, min.	-25 °C
Storage temperature, max.	55 °C

Connectable conductors

Clamping range, min.	0,13 mm ²
Clamping range, max.	2,5 mm ²
AWG, min.	26
AWG, max.	14
Solid, min. H05(07) V-U	0,13 mm ²
Solid, max. H05(07) V-U	2,5 mm ²
fine-stranded, min. H05(07) V-U	0,13 mm ²
fine-stranded, max. H05(07) V-U	2,5 mm ²
Wire end ferrule , DIN 46 228/1, min.	0,25 mm ²
Wire end ferrule , DIN 46 228/1, max.	1,5 mm ²
w. plastic collar ferrule, DIN 46228 pt 4, min.	0,25 mm ²
w. plastic collar ferrule, DIN 46228 pt 4, max.	1,5 mm ²

DIN IEC rating data

Rated current, min. No. pins (Tu=20°C)	24 A
Rated current, max. No. pins (Tu=20°C)	24 A
Rated current, min. No. pins (Tu=40°C)	24 A
Rated current, max. No. pins (Tu=40°C)	24 A
Rated voltage for overvoltage class/pollution severity II/2	600 V
Rated voltage for overvoltage class/pollution severity III/2	250 V
Rated voltage for overvoltage class/pollution severity III/3	250 V
Rated impulse withstand voltage for overvoltage class/pollution severity II/2	4 kV
Rated impulse withstand voltage for overvoltage class/pollution severity III/2	4 kV
Rated impulse withstand voltage for overvoltage class/pollution severity III/3	4 kV
Short-time withstand current resistance	3 x 1s with 120 A

CSA rating data

Rated voltage	300 V
Rated current	10 A
AWG conductor (field wiring), min.	26
AWG conductor (field wiring), max.	14

UL 1059 rating data

Rated voltage	300 V
Rated current	10 A
AWG conductor (field wiring), min.	26
AWG conductor (field wiring), max.	14

Approvals

Approval body



Downloads

CAD Library (P-CAD Format - ASCII)	PM.LIA
CAD Library (P-CAD Format - Standard)	PM.lib

Classifications

ETIM 2.0	NK
eClass 4.1	NK
eClass 5.0	NK
eClass 5.1	NK

- Rated current related to rated cross-section and min. No. of poles.
- Wire end ferrule without plastic collar to DIN 46228 pt 1
- Wire end ferrule with plastic collar to DIN 46228 pt 4
- The data given under CSA relates to a cUL approval - E60693
- P on drg. = pitch
- Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.

Related products

Order No.	Article designation	Number of poles
1760490000	PM 5.08/2/90 3.5 OR	2
1884320000	PM 5.08/2/90 3.5 GR	2
1760530000	PM 5.08/2/90 3.5 GN	2
1760500000	PM 5.08/3/90 3.5 OR	3
1760520000	PM 5.08/3/90 3.5 SW	3
1884330000	PM 5.08/3/90 3.5 GR	3
1760540000	PM 5.08/3/90 3.5 GN	3